

Specifications

Display 7" TFT LCD (capacitive touchscreen) Screen resolution 800 x 480

Built-in camera

PoE and + 12 V DC (PSU not included) Power

Power consumption 6 W, standby 2.5 W

Dimensions 195 x 127 x 27 mm Colors Black / White Plastic Body

Installation Type Wall mount

Mounting options Horizontal and vertical

Possibilities of connection

Number of individual Up to 9 panels

panels

Number of multiapartment panels

Connection of additional

monitors

Memory function

Interface

Number of IP cameras

Up to 9 panels

Up to 8 monitors

Record photo into internal memory (64 photo) Multi-language graphical and WEB interface

Up to 8 cameras

Main features



7" TFT display with capacitive touch



Record photo to internal memory



Screen Resolution 800×480



Support of receiving messages



Individual panels: up to 9 panels



Do Not Disturb



Multi-apartment panels: up to 9 panels



Silent mode



IP cameras: up to 8 cameras



Connection of the door bell



PoE and +12V DC



Horizontal and vertical mounting options

Functional capabilities

Intercom type Audio Intercom (no built-in camera)

Support of receiving messages

Yes

Select the type of screensaver

in standby mode

Single IP camera live viewing

Do Not Disturb Silent mode Yes, customizable by time


Yes

Software update From the web interface

From BAS-IP updates server

Color variations





Appearance and mechanical mounting

